

片口金蛍光ランプ(環形を含む) —
第 2 部 : 性能規定

正 誤 票

区分	位 置	誤	正							
本体	種別:FPL9	<table border="1"> <tr><td>口 金</td></tr> <tr><td>G10Xq-1</td></tr> </table>	口 金	G10Xq-1	<table border="1"> <tr><td>口 金</td></tr> <tr><td>GX10q-1</td></tr> </table>	口 金	GX10q-1			
	口 金									
	G10Xq-1									
	口 金									
	GX10q-1									
種別:FPL30	<table border="1"> <tr><td>口 金</td></tr> <tr><td>G10Yq-4</td></tr> </table>	口 金	G10Yq-4	<table border="1"> <tr><td>口 金</td></tr> <tr><td>GY10q-4</td></tr> </table>	口 金	GY10q-4				
口 金										
G10Yq-4										
口 金										
GY10q-4										
種別:FHT24 高周波点灯安定器 設計基準の欄	<table border="1"> <tr><td>A(A²s)</td><td>0.074</td></tr> <tr><td>IM(A)</td><td>0.256</td></tr> </table>	A(A ² s)	0.074	IM(A)	0.256	<table border="1"> <tr><td>A(A²s)</td><td>0.246</td></tr> <tr><td>IM(A)</td><td>0.328</td></tr> </table>	A(A ² s)	0.246	IM(A)	0.328
A(A ² s)	0.074									
IM(A)	0.256									
A(A ² s)	0.246									
IM(A)	0.328									
種別:FHT32 高周波点灯安定器 設計基準の欄	<table border="1"> <tr><td>A(A²s)</td><td>0.074</td></tr> <tr><td>IM(A)</td><td>0.256</td></tr> </table>	A(A ² s)	0.074	IM(A)	0.256	<table border="1"> <tr><td>A(A²s)</td><td>0.246</td></tr> <tr><td>IM(A)</td><td>0.328</td></tr> </table>	A(A ² s)	0.246	IM(A)	0.328
A(A ² s)	0.074									
IM(A)	0.256									
A(A ² s)	0.246									
IM(A)	0.328									
種別:FHT42 高周波点灯安定器 設計基準の欄	<table border="1"> <tr><td>A(A²s)</td><td>0.074</td></tr> <tr><td>IM(A)</td><td>0.256</td></tr> </table>	A(A ² s)	0.074	IM(A)	0.256	<table border="1"> <tr><td>A(A²s)</td><td>0.246</td></tr> <tr><td>IM(A)</td><td>0.328</td></tr> </table>	A(A ² s)	0.246	IM(A)	0.328
A(A ² s)	0.074									
IM(A)	0.256									
A(A ² s)	0.246									
IM(A)	0.328									

平成 19 年 1 月 5 日作成