

蛍光灯器具のエネルギー消費効率及び
固有エネルギー消費効率の算出方法

正 誤 票

区分	位置	誤									
附属書 2	附属書 2 表 9 管壁温度及び 温度補正係数	管壁温度及び温度補正係数									
		管壁 温度 ℃	温度補正 係数 %	管壁 温度 ℃	温度補正 係数 %	管壁 温度 ℃	温度補正 係数 %	管壁 温度 ℃	温度補正 係数 %		
		43	99.7/ ー	54	106.8/100.6	65	101.9/93.7	76	91.2/83.3		
		44	100.7/100.0	55	106.8/100.2	66	101.0/92.8	77	90.2/82.4		
		45	103.2/100.5	56	106.7/99.8	67	100.2/91.9	78	89.3/81.4		
		46	103.6/100.8	57	106.5/99.3	68	99.3/91.0	79	88.3/80.5		
		47	104.1/101.1	58	106.3/98.7	69	98.3/90.1	80	ー /79.6		
		48	104.5/101.3	59	105.9/98.1	70	97.3/89.1	81	ー /78.7		
		49	105.1/101.4	60	105.4/97.5	71	96.2/88.2	82	ー /77.8		
		50	105.7/101.4	61	104.9/96.8	72	95.2/87.2	83	ー /76.9		
		51	106.1/101.3	62	104.2/96.1	73	94.2/86.2				
		52	106.5/101.1	63	103.4/95.3	74	93.2/85.3				
		53	106.7/100.9	64	102.8/94.5	75	92.2/84.3				
		注記 温度補正係数欄は、定格点灯時の値／高出力点灯時の値を示す。									
		正									
				管壁温度及び温度補正係数							
				管壁 温度 ℃	温度補正 係数 %	管壁 温度 ℃	温度補正 係数 %	管壁 温度 ℃	温度補正 係数 %	管壁 温度 ℃	温度補正 係数 %
				41	ー /100.0	52	106.5/103.8	63	103.4/96.7	74	93.2/86.3
				42	ー /101.1	53	106.7/103.5	64	102.8/95.8	75	92.2/85.4
				43	99.7/101.6	54	106.8/103.1	65	101.9/94.8	76	91.2/84.5
44	100.7/102.4			55	106.8/102.5	66	101.0/94.0	77	90.2/83.6		
45	103.2/103.0			56	106.7/102.0	67	100.2/92.8	78	89.3/82.9		
46	103.6/103.4			57	106.5/101.3	68	99.3/91.9	79	88.3/ ー		
47	104.1/103.7			58	106.3/100.7	69	98.3/91.0				
48	104.5/103.8			59	105.9/99.9	70	97.3/90.1				
49	105.1/104.1			60	105.4/99.2	71	96.2/89.2				
50	105.7/104.0			61	104.9/98.3	72	95.2/88.3				
51	106.1/103.9			62	104.2/97.5	73	94.2/87.2				
注記 温度補正係数欄は、定格点灯時の値／高出力点灯時の値を示す。											