

Translated and Published by Japanese Standards Association

# JIS C 1736-1:2021

## (JEMA/JSA)

Instrument transformers for metering service — Part 1: General measuring instrument

Date of Establishment: 2009-04-20 Date of Revision: 2021-03-22 Date of Public Notice in Official Gazette: 2021-03-22

Investigated by: Japanese Industrial Standards Committee

Standards Board for IEC area

Technical Committee on Electricity

JIS C1736-1: 2021, First English edition published in 2023-06

Translated and published by: Japanese Standards Association Mita MT Building, 3-13-12, Mita, Minato-ku, Tokyo, 108-0073 JAPAN

> In the event of any doubts arising as to the contents, the original JIS is to be the final authority.

© JSA 2023

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

KK/HN

#### Contents

### Page

1	Scope1		
2	Normative reference ······1		
3	Terms and definitions1		
3.1	Terms relating to general terms		
	Terms relating to general terms		
3.2	Terms relating to current transformer ···································		
3.3	Terms relating to voltage transformer and combined instrument		
	transformer ······6		
4	Service condition		
4.1	Standard service condition7		
4.2	Special service condition7		
~	Structure		
5			
5.1	General ·····8		
5.2	Mechanical strength ······8		
5.3	Insulating tubes		
5.4	Internal structure ······8		
5.5	Sealing structure ······8		
5.6	Sealing		
5.7	Polarity ·····9		
6	Ratings ······9		
6.1	Maximum voltage ······9		
6.2	Rated current		
6.3	Rated voltage ······10		
6.4	Rated withstand current11		
6.5	Accuracy class ······12		
6.6	Rated burden ······12		
6.7	Rated frequency ······13		
7	Performance ······13		
7.1	Withstand current ······13		
7.2	Secondary short-circuit ······14		
7.3	Temperature rise ······14		
7.4	Withstand voltage ······15		
7.5	Abnormal phenomenon ·····19		
7.6	Resultant error ······20		
7.7	Current characteristics ······21		
7.8	Voltage characteristics ······22		
7.9	Frequency characteristics		
7.10	Mutual interference		

$7.11 \\ 7.12 \\ 7.13$	Gas leak amount ·····23 Purity of gas ·····23 Moisture content in gas ····23		
8 8.1 8.2 8.3	Test23Classification of test23Test items and gas pressure during test23Test method27		
9 9.1 9.2	Terminal43Symbol of terminal43Position of terminal52		
10 10.1 10.2 10.3 10.4	Marking53General53Current transformer57Voltage transformer59Combined instrument transformer60		
11	Current transfor	rmer for multi-circuit summation meter61	
Annex	A (normative)	Method for obtaining resultant error of instrument transformer	
Annex	x B (normative)	Current density and initial temperature used for temperature rise calculation formula of thermal with- stand current test	
Annex	c C (normative)	Current transformer for multi-circuit summation meter	

#### Foreword

This Japanese Industrial Standard has been revised by the Minister of Economy, Trade and Industry through deliberations at the Japanese Industrial Standards Committee as the result of proposal for revision of Japanese Industrial Standard submitted by The Japan Electrical Manufacturers' Association (JEMA)/Japanese Standards Association (JSA) with a draft being attached, based on the provision of Article 12, paragraph (1) of the Industrial Standardization Act applied mutatis mutandis pursuant to the provision of Article 16 of the said Act. This edition replaces the previous edition (JIS C 1736-1: 2009), which has been technically revised.

This **JIS** document is protected by the Copyright Act.

Attention is drawn to the possibility that some parts of this Standard may conflict with patent rights, published patent application or utility model rights. The relevant Minister and the Japanese Industrial Standards Committee are not responsible for identifying any of such patent rights, published patent application or utility model rights.

JIS C 1736 series consists of the following 2 parts under the general title *Instrument transformers for metering service*:

- JIS C 1736-1 Part 1: General measuring instrument
- JIS C 1736-2 Part 2: Measuring instruments used in transaction or certification

# Blank

### Instrument transformers for metering service — Part 1 : General measuring instrument

#### 1 Scope

This Standard specifies requirements for the instrument transformers for metering service used in combination with a watt-hour meter, a var-hour meter or a maximum demand watt-hour meter at the commercial frequency.

#### 2 Normative reference

There are no normative references in this Standard.

#### 3 Terms and definitions

For the purpose of this Standard, the following terms and definitions apply.

#### 3.1 Terms relating to general terms

#### 3.1.1

#### instrument transformer

equipment for current and voltage transformation to be used together with a watt-hour meter, a var-hour meter or a maximum demand watt-hour meter

NOTE It is a general term of a current transformer, a voltage transformer and a combined instrument transformer.

#### 3.1.2

#### dry type instrument transformer

instrument transformer of which the principal components such as an iron core and winding are used in the air

#### 3.1.3

#### mould type instrument transformer

instrument transformer of which the entire surface of winding is covered with resin or insulating material containing resin among dry type instrument transformers

#### 3.1.4

#### oil-immersed instrument transformer

instrument transformer of which the principal components such as an iron core and winding are immersed in insulating oil

#### 3.1.5

#### gas insulated instrument transformer