

Translated and Published by Japanese Standards Association

 $JIS \, C \, 2805 \, : \, 2010$ 

(JEMA/JSA)

Crimp-type terminal lugs for copper conductors

ICS 29.120.20

Reference number: JIS C 2805: 2010 (E)

C 2805: 2010

Date of Establishment: 1969-07-01

Date of Revision: 2010-10-20

Date of Public Notice in Official Gazette: 2010-10-20

Investigated by: Japanese Industrial Standards Committee

Standards Board

Technical Committee on Electricity Technology

JIS C 2805:2010, First English edition published in 2011-12

Translated and published by: Japanese Standards Association 4-1-24, Akasaka, Minato-ku, Tokyo, 107-8440 JAPAN

In the event of any doubts arising as to the contents, the original JIS is to be the final authority.

### © JSA 2011

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

NH/AT

## Contents

|        | Page  |
|--------|---|
| Intro  | duction1  |
| 111610 |   |
| 1      | Scope1  |
| 2      | Normative references ···································· |
| 3      | Classification, symbol and nominal size2                  |
| 4      | Performance 2   |
| 4.1    | Secureness of crimped connection2                         |
| 4.2    | Temperature rise ————————————————————————————————————     |
| 4.3    | Cyclic heating2   |
| 4.4    | Electrical resistance                                     |
| 4.5    | Salt spray 3  |
| 4.6    | Overcurrent withstand3                                    |
| 4.7    | Tensile strength ······ 3                                 |
| 4.8    | Vibration fatigue ····································    |
| 4.9    | Insulation resistance3                                    |
| 4.10   | Dielectric withstand voltage3                             |
| 4.11   | Resistance to aging                                       |
| 4.12   | Secureness of insulant ······ 4                           |
| 4.13   | Flame retardancy ······ 4                                 |
| 4.14   | Resistance to oil4  |
| 4.15   | Secureness of crimped connection at low temperature4      |
| 5      | Appearance, dimensions and metallic coating4              |
| 6      | Material and manufacturing method4                        |
| 6.1    | Material ······ 4   |
| 6.2    | Manufacturing method5                                     |
| 7      | Test method ····· 5                                       |
| 7.1    | Testing conditions5                                       |
| 7.2    | Appearance test ·································         |
| 7.3    | Dimension test ··································         |
| 7.4    | Thickness test of metallic coating8                       |
| 7.5    | Secureness test of crimped connection8                    |
| 7.6    | Temperature rise test ································    |
| 7.7    | Cyclic heating test9                                      |
| 7.8    | Electrical resistance test ·····················10        |
| 7.9    | Salt spray test ——————————————————————————————————        |
| 7.10   | Overcurrent withstand test                                |
| 7.11   | Tensile strength test ··································  |

### C 2805:2010

| 7.12 | Vibration fatigue test ······                            | ·· 13            |
|------|--|------------------|
| 7.13 | Insulation resistance test                               | 14               |
| 7.14 | Dielectric withstand voltage test                        | 14               |
| 7.15 | Aging test   | 14               |
| 7.16 | Insulant secureness test                                 | ·· 15            |
| 7.17 | Flame retardancy test                                    | $\cdot \cdot 15$ |
| 7.18 | Oil resistance test                                      | 16               |
| 7.19 | Secureness test of crimped connection at low temperature | 16               |
| 8    | Inspection   | 16               |
| 8.1  | Type inspection  | 16               |
| 8.2  | Acceptance inspection ·····                              | $\cdot \cdot 17$ |
| 9    | Designation of product                                   | 18               |
| 10   | Marking  | 18               |
| 10.1 | Marking on product                                       | 18               |
| 10.2 | Marking on packaging                                     | 18               |

### Foreword

This translation has been made based on the original Japanese Industrial Standard revised by the Minister of Economy, Trade and Industry, through deliberations at the Japanese Industrial Standards Committee as the result of proposal for revision of Japanese Industrial Standard submitted by The Japan Electrical Manufacturers' Association (JEMA)/Japanese Standards Association (JSA) with the draft being attached, based on the provision of Article 12 Clause 1 of the Industrial Standardization Law applicable to the case of revision by the provision of Article 14.

Consequently JIS C 2805: 2003 has been replaced with this Standard.

However, **JIS C 2805**:2003 may be applied in the **JIS** mark certification based on the relevant provisions of Article 19 Clause 1, etc. of the Industrial Standardization Law until October 19th, 2011.

This **JIS** document is protected by the Copyright Law.

Attention is drawn to the possibility that some parts of this Standard may conflict with a patent right, application for a patent after opening to the public, utility model right or application for registration of utility model after opening to the public which have technical properties. The relevant Minister and the Japanese Industrial Standards Committee are not responsible for identifying the patent right, application for a patent after opening to the public, utility model right or application for registration of utility model after opening to the public which have the said technical properties.

# Crimp-type terminal lugs for copper conductors

JIS C 2805: 2010

### Introduction

This Japanese Industrial Standard was established in 1969 and has gone through six revisions to this day. The last revision was taken place in 2003, and the revision at this time is to correspond to the diversification of insulant materials afterwards.

The corresponding International Standard has not yet been published at this moment.

### 1 Scope

This Standard specifies the non-insulated crimp-type terminal lugs which are crimped directly and the insulated crimp-type terminal lugs which are crimped through the insulant thereof (hereafter referred to as "non-insulated terminal lugs" and "insulated terminal lugs", respectively, and as "terminal lugs" for both types in generic term) which are intended for connection of annealed copper stranded wires or solid wires principally used as the internal wiring of electric power machine and apparatus and the mutual wiring among such machines and apparatuses, in such a manner that the terminal lug is connected to the end of wire using the connecting tool specified in **JIS C** 9711 or that assigned by the terminal lug manufacturer (hereafter referred to as "tool").

NOTE: The insulated terminal lugs specified in this Standard are those used for the wiring of control circuit or the like.

### 2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this Standard. The most recent editions of the standards (including amendments) indicated below shall be applied.

| JIS B 4652 | Hand torque tools—Requirements and test methods          |
|------------|--|
| JIS B 7507 | Vernier, dial and digital callipers                      |
| JIS C 1302 | Insulation resistance testers                            |
| JIS C 1602 | Thermocouples  |
| JIS C 2320 | Electrical insulating oils                               |
| JIS C 3307 | 600 V Polyvinyl chloride insulated wires                 |
| JIS C 9711 | Compression tools for wire connectors of interior wiring |
| JIS H 3100 | Copper and copper alloy sheets, plates and strips        |
| JIS H 8501 | Methods of thickness test for metallic coatings          |
| JIS H 8619 | Electroplated coatings of tin                            |
| JIS K 2240 | Liquefied petroleum gases                                |
| JIS Z 2371 | Methods of salt spray testing                            |