



JAPANESE
INDUSTRIAL
STANDARD

Translated and Published by
Japanese Standards Association

JIS C 4213 : 2014

(JEMA)

**Low-voltage three-phase
squirrel-cage induction motors—
Low-voltage top runner motor**

ICS 29.160.30

Reference number : JIS C 4213 : 2014 (E)

Date of Establishment: 2014-03-20

Date of Public Notice in Official Gazette: 2014-03-20

Investigated by: Japanese Industrial Standards Committee
Standards Board

Technical Committee on Electricity Technology

JIS C 4213:2014, First English edition published in 2016-12

Translated and published by: Japanese Standards Association
Mita MT Building, 3-13-12, Mita, Minato-ku, Tokyo, 108-0073 JAPAN

In the event of any doubts arising as to the contents,
the original JIS is to be the final authority.

© JSA 2016

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

KK/AT

Contents

	Page
Introduction.....	1
1 Scope	1
2 Normative references	2
3 Terms and definitions	3
4 Duty	5
4.1 Duty	5
4.2 Duty types	5
5 Rating	7
5.1 Rated voltage	7
5.2 Rated frequency	7
5.3 Rated output	8
6 Conditions for installation site	8
6.1 General matters	8
6.2 Altitude	8
6.3 Maximum ambient temperature	8
6.4 Minimum ambient temperature	8
6.5 Water coolant temperature	8
6.6 Storage and transport	8
7 Performances	8
7.1 Temperature rise	8
7.2 Reference coolant	11
7.3 Efficiency	12
7.4 Withstand voltage	15
7.5 Voltage variation and frequency variation during operation	16
8 Construction	17
8.1 Accessories	17
8.2 Cable entrance	17
8.3 Earthing terminal	17
8.4 Protection method	17
9 Dimensions	17
10 Test methods	21
10.1 Types of test	21
10.2 Structure test	22
10.3 Resistance value	22
10.4 Lock test	23

10.5	Temperature rise	24
10.6	Determination of efficiency	27
10.7	Determination of starting property	27
10.8	Overspeed test	30
10.9	Noise test	31
10.10	Withstand voltage test	35
11	Tolerance	37
12	Marking	38
13	Safety	39
Annex JA (informative)	Relation between typical frame number and dimensions, and output	40
Annex JB (informative)	Comparison table between JIS and corresponding International Standards	49

Foreword

This translation has been made based on the original Japanese Industrial Standard established by the Minister of Economy, Trade and Industry through deliberations at the Japanese Industrial Standards Committee according to the proposal for establishment of Japanese Industrial Standard submitted by The Japan Electrical Manufacturers' Association (JEMA) with the draft being attached, based on the provision of Article 12 Clause 1 of the Industrial Standardization Law.

This **JIS** document is protected by the Copyright Law.

Attention is drawn to the possibility that some parts of this Standard may conflict with patent rights, applications for a patent after opening to the public or utility model rights. The relevant Minister and the Japanese Industrial Standards Committee are not responsible for identifying any of such patent rights, applications for a patent after opening to the public or utility model rights.

Low-voltage three-phase squirrel-cage induction motors—Low-voltage top runner motor

Introduction

This Japanese Industrial Standard has been prepared based on the twelfth edition of **IEC 60034-1** published in 2010, the third edition of **IEC 60034-8** published in 2007, Edition 4.1 of **IEC 60034-9** published in 2007, Edition 2.1 of **IEC 60034-12** published in 2007 and the sixth edition of **IEC 60072-1** published in 1991 with some modifications of the technical contents such as the deletion of the specifications relating to inapplicable items.

The portions given sidelines or dotted underlines are the matters in which the contents of the corresponding International Standards have been modified. A list of modifications with the explanations is given in Annex JB. The matters contained in Annex JA are unique contents of **JIS** that are not given in the corresponding International Standards.

1 Scope

This Standard specifies the low-voltage top runner motors (hereafter referred to as motors) among the low-voltage three-phase 50 Hz and/or 60 Hz squirrel-cage induction motors shown below. This Standard covers the motors having the ratings of two or more voltages and/or frequencies.

- Rated voltage 600 V or under
- Rated output 0.75 kW or over up to and including 375 kW
- 2, 4 or 6 poles
- Duty type S1 (continuous running duty) or S3 (intermittent periodic duty) having 80 % or more cyclic duration factor
- Commercial power source driven type
- Motors suitable for conditions of installation site specified in clause 6

This Standard also covers the following motors.

- Motors having flange, foot or shaft of special dimensions
- Motors incorporated in geared motors and brake motors irrespective of the shapes of shafts and/or flanges

This Standard does not cover the following motors.

- Motors that are driven exclusively by inverter.
- Motors which are completely integrated into a machine (for example, pump, fan and compressor) therefore which cannot be tested separately from the machine