

JAPANESE INDUSTRIAL STANDARD

Translated and Published by Japanese Standards Association

JIS C 4620: 2023

(JEA/JSA)

Cubicle type high voltage power receiving units

ICS 29.240.10

Reference number: JIS C 4620: 2023 (E)

C 4620: 2023

Date of Establishment: 1968-12-01

Date of Revision: 2023-12-20

Date of Public Notice in Official Gazette: 2023-12-20

Investigated by: Japanese Industrial Standards Committee

Standards Board for IEC area

JIS C 4620 : 2023, First English edition published in 2025-03

Translated and published by: Japanese Standards Association Mita Avanti, 3-11-28, Mita, Minato-ku, Tokyo, 108-0073 JAPAN

In the event of any doubts arising as to the contents, the original JIS is to be the final authority.

© JSA 2025

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan HN

Contents

			Page
1	Scope ·····		1
2	Normative references · · · · · · · · · · · · · · · · · · ·		
3	Terms and definitions		
4 4.1 4.2	Service conditions Standard service conditions Special service conditions		
5	Classification		6
6 6.1 6.2 6.3 6.4 6.5 6.6	Performances7Coordination of operation7Breaking performance7Operation7Temperature rise7Dielectric withstand voltage8Waterproof property9		
7 7.1 7.2 7.3 7.4 7.5	Construction and equipment9Construction in general9Enclosure, etc.10Configuration and mounting of equipment11Wiring and connection of equipment15Ventilation19		
8 8.1 8.2	Shapes and dimensions 20 Shapes 20 Dimensions 20		·20
9	Equipment and	materials ·····	·20
10 10.1 10.2 10.3	Tests 22 Classification of tests 22 Test items 22 Test methods 23		·22 ·22
11	Designation of products · · · · · · · · · · · · · · · · · · ·		·24
12	Marking ·····		.24
Annex A (normative)		Mould type current transformers used for cubicle type high voltage power receiving units	·33
Annex B (normative)		Method for obtaining overcurrent constant	·36

C 4620: 2023

Annex C (normative)	Primary cutout switch ······ 39
Annex D (normative)	Wire supports ······ 44
Annex E (normative)	Waterproof test of cubicle type high voltage power receiving units · · · · · · · 46
Annex F (normative)	Temperature rise test of cubicle type high voltage power receiving units · · · · · 51
Annex G (informative)	Examples of external dimensions of cubicle54

Foreword

This Japanese Industrial Standard has been revised by the Minister of Economy, Trade and Industry through deliberations at the Japanese Industrial Standards Committee as the result of proposal for revision of Japanese Industrial Standard submitted by The Japan Electric Association (JEA)/Japanese Standards Association (JSA) with a draft being attached, based on the provision of Article 12, paragraph (1) of the Industrial Standardization Act applied mutatis mutandis pursuant to the provision of Article 16 of the said Act. This edition replaces the previous edition (JIS C 4620: 2018), which has been technically revised.

This **JIS** document is protected by the Copyright Act.

Attention is drawn to the possibility that some parts of this Standard may conflict with patent rights, published patent application or utility model rights. The relevant Minister and the Japanese Industrial Standards Committee are not responsible for identifying any of such patent rights, published patent application or utility model rights.

Blank

Cubicle type high voltage power receiving units

JIS C 4620: 2023

1 Scope

This Japanese Industrial Standard specifies requirements for cubicle type high voltage power receiving units (hereafter referred to as cubicles) not exceeding 4 000 kVA in the capacity of power receiving unit, intended for use by consumers to receive electrical power from general transmission and distribution companies, specific transmission and distribution companies (hereafter referred to as general transmission and distribution companies, etc.). They are used in a circuit with a system short-circuit current not exceeding 12.5 kA at a nominal voltage of 6.6 kV and at a frequency of 50 Hz or 60 Hz.

2 Normative references

Part or all of the provisions of the following standards, through reference in this text, constitute provisions of this Standard. The most recent editions of the standards (including amendments) indicated below shall be applied.

- JIS C 0446 Identification of conductors by colours or numerals
- JIS C 1102-1 Direct acting indicating analogue electrical measuring instruments and their accessories Part 1: Definitions and general requirements common to all parts
- JIS C 1102-2 Direct acting indicating analogue electrical measuring instruments and their accessories Part 2: Special requirements for ammeters and voltmeters
- JIS C 1102-3 Direct acting indicating analogue electrical measuring instruments and their accessories Part 3: Special requirements for wattmeters and varmeters
- JIS C 1102-4 Direct acting indicating analogue electrical measuring instruments and their accessories Part 4: Special requirements for frequency meters
- JIS C 1102-5 Direct acting indicating analogue electrical measuring instruments and their accessories Part 5: Special requirements for phase meters, power factor meters and synchroscopes
- JIS C 1102-6 Direct acting indicating analogue electrical measuring instruments and their accessories Part 6: Special requirements for ohmmeters (impedance meters) and conductance meters
- JIS C 1102-7 Direct acting indicating analogue electrical measuring instruments and their accessories Part 7: Special requirements for multi-function instruments