

Translated and Published by Japanese Standards Association

JIS C 8711: 2019

(BAJ/JSA)

Secondary cells and batteries containing alkaline or other non-acid electrolytes—Secondary lithium cells and batteries for portable applications

ICS 29.220.99

 $Reference\ number:\ JIS\ C\ 8711:2019\ (E)$

C 8711: 2019

Date of Establishment: 2000-12-20

Date of Revision: 2019-11-20

Date of Public Notice in Official Gazette: 2019-11-20

Investigated by: Japanese Industrial Standards Committee

Standards Board for IEC area

JIS C 8711:2019, First English edition published in 2020-06

Translated and published by: Japanese Standards Association Mita MT Building, 3-13-12, Mita, Minato-ku, Tokyo, 108-0073 JAPAN

In the event of any doubts arising as to the contents, the original JIS is to be the final authority.

© JSA 2020

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

Contents

	Page
Introduction	
1	Scope1
2	Normative references — 2
3	Terms and definitions ————————————————————————————————————
4	Parameter measurement tolerances ······· 4
5 5.1 5.2 5.3	Cell designation and marking4Secondary lithium cell and battery designation4Marking6Design and produce requirement of batteries7
6	Examples of cells7
7 7.1 7.2 7.3 7.4 7.5 7.6 7.7 7.8	Electrical tests and required characteristics8General8Charging procedure for test purposes10Discharge performance test10Charge (capacity) retention and recovery11Charge (capacity) recovery after long term storage12Endurance in cycles12Battery internal resistance13Electrostatic discharge (ESD)15
7A	Mechanical tests and required characteristics15
7B	Safety tests and required characteristics
8 8.1 8.2	Test protocol and conditions for type approval
Anne	ex A (informative) Dimensions of the cell with a laminate film case ············ 17
Anne	ex B (informative) Capacity after storage19
Annex JA (informative) Comparison table between JIS and corresponding International Standard20	

Foreword

This Japanese Industrial Standard has been revised by the Minister of Economy, Trade and Industry through deliberations at the Japanese Industrial Standards Committee as the result of proposal for revision of Japanese Industrial Standard submitted by Battery Association of Japan (BAJ)/Japanese Standards Association (JSA) with a draft being attached, based on the provision of Article 12, paragraph (1) of the Industrial Standardization Act applied mutatis mutandis pursuant to the provision of Article 16 of the said Act. This edition replaces the previous edition (**JIS C 8711**:2013), which has been technically revised.

This **JIS** document is protected by the Copyright Act.

Attention is drawn to the possibility that some parts of this Standard may conflict with patent rights, published patent application or utility model rights. The relevant Minister and the Japanese Industrial Standards Committee are not responsible for identifying any of such patent rights, published patent application or utility model rights.

Secondary cells and batteries containing alkaline or other non-acid electrolytes— Secondary lithium cells and batteries for portable applications

JIS C 8711:2019

Introduction

This Japanese Industrial Standard has been prepared based on **IEC 61960-3**:2017, Edition 1, with some modifications of the technical contents.

The vertical lines on both sides and dotted underlines indicate changes from the corresponding International Standard. A list of modifications with the explanations is given in Annex JA.

1 Scope

This Standard specifies requirements for secondary lithium single cells and secondary lithium batteries (hereafter referred to as secondary lithium cells and batteries) for portable applications.

The objective of this Standard is to provide the purchasers and users of secondary lithium cells and batteries with a set of criteria with which they can judge the performance of secondary lithium cells and batteries offered by various manufacturers.

Portable applications comprise hand-held equipment, transportable equipment and movable equipment.

Examples of the main portable applications are shown below:

- a) hand-held equipment: smartphone, tablet PCs, audio/video players, and similar equipment;
- b) transportable equipment: notebook computers, CD players, and similar equipment;
- c) movable equipment: either of the following:
 - 18 kg or less in mass and not fixed in place;
 - provided with wheels, castors, or other similar means to facilitate movement by an ordinary person as required to perform its intended use;
 - power tools, power assisted cycles, business-use video cameras, and similar equipment.
 - NOTE 1 All applications using batteries whose nominal voltages are equal to or over the hazardous voltage of 60 V DC are excluded.
 - NOTE 2 EESS (Electrical Energy Storage Systems) and UPS, which use batteries over 500 Wh of electric energy are excluded.
 - NOTE 3 Self-propelled vehicles are excluded.

This Standard defines a minimum required level of performance and a standardized methodology by which testing is performed and the results of this testing reported to the user. Hence, users will be able to establish the viability of commercially available