

Translated and Published by Japanese Standards Association

JIS C 9613^{:2021} (JEMA) Hairdryers

ICS 97.170 Reference number : JIS C 9613 : 2021 (E)

Date of Establishment: 1969-12-01

Date of Revision: 2021-09-21

Date of Public Notice in Official Gazette: 2021-09-21

Investigated by: Japanese Industrial Standards Committee

Standards Board for IEC area

Technical Committee on Electricity

JIS C 9613 : 2021, First English edition published in 2022-12

Translated and published by: Japanese Standards Association Mita MT Building, 3-13-12, Mita, Minato-ku, Tokyo, 108-0073 JAPAN

> In the event of any doubts arising as to the contents, the original JIS is to be the final authority.

© JSA 2022

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

AH/HN

Contents

Page

1	Scope1
2	Normative references · · · · · · 1
3	Terms and definitions ······2
4 4.1	Operating performance and shape 2 Starting 2
4.2 4.3	Voltage fluctuation 2 Power consumption 2
4.3 4.4	Air speed ······2
4.5	Noise 2
4.6	Air volume ·····2
5	Safety performance
5.1	Temperature ······3
5.2	Insulation 4
5.3	Leakage current
5.4 5.5	Resistance to shock by fall
5.5 5.6	Switch
5.0 5.7	Flexure of cord
5.8	Endurance of cord reel mechanism ······6
6	Construction ·······6
6.1	Construction in general ····································
6.2	Live part ·····8
6.3	Electrical insulating material10
6.4	Wiring ······10
6.5	Components ······12
7	Materials ······13
8	Performance tests ······14
8.1	Standard test conditions ······14
8.2	Starting test ······14
8.3	Voltage fluctuation test ······14
8.4	Power consumption test ······14
8.5 8.C	Air speed test ··································
8.6 9.7	Noise test
0.1	Air volume test method
9	Safety tests ······17
9.1	Normal temperature test ······17

9.2	Abnormal temperature test ······18	
9.3	Insulation resistance test ······18	
9.4	Dielectric withstand voltage test ······18	
9.5	Leakage current test ······18	
9.6	Resistance to shock by fall	
9.7	Endurance test ······19	
9.8	Switch test ······19	
9.9	Flexure test of cord ······19	
9.10	Endurance test of cord reel mechanism22	
10	Inspections ······22	
10.1	Type inspection ······22	
10.2	Product inspection	
11	Designation of products ······23	
12	Marking ·····23	
12.1	Marking on product23	
12.2	Marking on package ······24	
13	Precaution for use ······24	
Annex A (normative) Hairdryer (Type B)25		

Foreword

This Japanese Industrial Standard has been revised by the Minister of Economy, Trade and Industry through deliberations at the Japanese Industrial Standards Committee as the result of proposal for revision of Japanese Industrial Standard submitted by The Japan Electrical Manufacturers' Association (JEMA) with a draft being attached, based on the provision of Article 12, paragraph (1) of the Industrial Standardization Act applied mutatis mutandis pursuant to the provision of Article 16 of the said Act. This edition replaces the previous edition (JIS C 9613 : 2007), which has been technically revised.

This **JIS** document is protected by the Copyright Act.

Attention is drawn to the possibility that some parts of this Standard may conflict with patent rights, published patent application or utility model rights. The relevant Minister and the Japanese Industrial Standards Committee are not responsible for identifying any of such patent rights, published patent application or utility model rights.

Blank

Hairdryers

1 Scope

This Japanese Industrial Standard specifies requirements for hand-held hairdryers (hereafter referred to as equipment) with a built-in blower and electric heater of which rated voltage is 300 V or under for single phase a.c., rated frequency is 50 Hz and/or 60 Hz, and rated power consumption is 1 500 W or under, excluding hairdryers for special purposes, such as steam type and iron type.

This Standard specifies requirements for the following different types of hairdryers separately in the main body and in Annex A, depending on the applicable standards.

- a) Type A : Standards unique to Japan are applied.
- b) Type B: Standards of **JIS C 9335-2-23** are applied.
 - NOTE Standards unique to Japan refers to the interpretation of the technical standards of the Electrical Appliances and Materials Safety Act (Appended Table 8 standards).

When requirements in the main body (Type A) are applied, the requirements in Annex A (Type B) do not apply. Similarly, when requirements in Annex A (Type B) are applied, requirements in the main body (Type A) do not apply.

2 Normative references

Part or all of the provisions of the following standards, through reference in this text, constitute provisions of this Standard. The most recent editions of the standards (including amendments) indicated below shall be applied.

- JIS C 1509-1 Electroacoustics Sound level meters Part 1 : Specifications
- JIS C 1509-2 Electroacoustics Sound level meters Part 2 : Pattern evaluation tests
- JIS C 2520 Wires and rolled wires for electrical heating

JIS C 3301 Rubber insulated flexible cords

JIS C 3306 Polyvinyl chloride insulated flexible cords

JIS C 5101 (all parts) Fixed capacitors for use in electronic equipment

- JIS C 8303 Plugs and receptacles for domestic and similar general use
- JIS C 8358 Appliance couplers for domestic and similar use

JIS C 9335-2-23 Household and similar electrical appliances — Safety — Part 2-23 : Particular requirements for appliances for skin or hair care

JIS C 9603 Ventilating fans

JIS K 2240 Liquefied petroleum gases

PROTECTED BY COPYRIGHT