

Translated and Published by Japanese Standards Association

JIS G 3477-2:2022

(JISF)

Polyethylene coated steel pipes — Part 2: External extruded polyethylene coated steel pipes

Date of Establishment: 2012-11-20 Date of Revision: 2022-12-20 Date of Public Notice in Official Gazette: 2022-12-20 Developed by: The Japan Iron and Steel Federation Investigated by: The Japan Iron and Steel Federation, Standardization Center

JIS G 3477-2 : 2022, First English edition published in 2023-07

Translated and published by: Japanese Standards Association Mita MT Building, 3-13-12, Mita, Minato-ku, Tokyo, 108-0073 JAPAN

> In the event of any doubts arising as to the contents, the original JIS is to be the final authority.

© JSA 2023

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

Contents

Page

1	Scope1	
2	Normative references · · · · · · 1	
3	Terms and definitions	
4	Symbols of grade ····································	
$5 \\ 5.1 \\ 5.2$	Materials ······ 3 Original pipes ····· 3 Coating materials ····· 4	
6 6.1 6.2 6.3	Manufacturing method 4 Pretreatment 4 Coating method 4 Inner coating 4	
7 7.1 7.2 7.3 7.4	Coated steel pipes4Coating performance4Coating thickness5Position and shape of coating at pipe end6Appearance7	
8 8.1 8.2 8.3 8.4 8.5 8.6 8.7 8.8	Tests of coated steel pipes7Type of test7Coating thickness test8Pinhole test8Adhesive property test8Peel strength test8Impact test8Indentation depth test9Bend test9	
9	Inspection ·····9	
10	Marking ······9	
11	Information to be supplied by the purchaser	
12	Report ·····10	
Annex	A (normative) Polyethylene coating materials11	
Annex B (normative) Adhesives ······13		
Annex C (normative) Tackifier		
Annex D (normative) Coating thickness measurement method16		

Annex E (normative)	Peel strength test method
Annex F (normative)	Impact test method ······18
Annex G (normative)	Indentation depth test method19
Annex H (normative)	Bend test method ······20

Foreword

This Japanese Industrial Standard has been revised by the Minister of Economy, Trade and Industry based on the provision of Article 14, paragraph (1) of the Industrial Standardization Act applied mutatis mutandis pursuant to the provision of Article 16 of the said Act in response to a proposal for revision of Japanese Industrial Standard with a draft being attached, submitted by The Japan Iron and Steel Federation (JISF), an accredited standards development organization. This edition replaces the previous edition (**JIS G 3477-2** : 2018), which has been technically revised.

However, **JIS G 3477-2**: 2018 may be applied in the **JIS** mark certification based on the relevant provisions of Article 30, paragraph (1), etc. of the Industrial Standardization Act until 19 December 2023.

This **JIS** document is protected by the Copyright Act.

Attention is drawn to the possibility that some parts of this Standard may conflict with patent rights, published patent application or utility model rights. The relevant Minister is not responsible for identifying any of such patent rights, published patent application or utility model rights.

JIS G 3477 series consists of the following 3 parts under the general title *Polyethylene coated steel pipes*:

Part 1: External 3 layer extruded polyethylene coated steel pipes

Part 2: External extruded polyethylene coated steel pipes

Part 3: External polyethylene powder coated steel pipes

Blank

Polyethylene coated steel pipes — Part 2: External extruded polyethylene coated steel pipes

1 Scope

This Japanese Industrial Standard specifies requirements for the external extruded polyethylene coated steel pipes (hereafter referred to as coated steel pipes) mainly used for underground services (including the bottom of river, the bottom of sea and common ditch) of transporting gas, oil, water, etc. and protecting cables.

- NOTE 1 This Standard is applicable to pipes of outside diameter 21.7 mm (nominal diameter 15A or 1/2B) to 812.8 mm (nominal diameter 800A or 32B) (see Table 2).
- NOTE 2 The coated steel pipes are usually used at temperatures in the range of -20 °C to +40 °C.

2 Normative references

Part or all of the provisions of the following standards, through reference in this text, constitute provisions of this Standard. The most recent editions of the standards (including amendments) indicated below shall be applied.

JIS G 0202	Glossary of terms used in iron and steel (Testing)		
JIS G 0203	Glossary of terms used in iron and steel (Products and quality)		
JIS G 0404	$Steel \ and \ steel \ products - General \ technical \ delivery \ requirements$		
JIS G 0415	Steel and steel products — Inspection documents		
JIS G 3444	Carbon steel tubes for general structure		
JIS G 3445	Carbon steel tubes for machine structure		
JIS G 3452	Carbon steel pipes for ordinary piping		
JIS G 3454	Carbon steel pipes for pressure service		
JIS G 3455	Carbon steel pipes for high pressure service		
JIS G 3457	Arc welded carbon steel pipes		
JIS G 3460	Steel pipes for low temperature service		
JIS K 2207	Petroleum asphalts		
JIS K 2235	Petroleum waxes		
JIS K 5500	Glossary of terms for coating materials		
JIS K 6900	Plastics — Vocabulary		
JIS K 6922-2 Plastics — Polyethylene (PE) moulding and extrusion materials			

PROTECTED BY COPYRIGHT