



JAPANESE
INDUSTRIAL
STANDARD

Translated and Published by
Japanese Standards Association

JIS H 8682-2 : 2013

(JAPA/JSA)

**Anodizing of aluminium and its
alloys—Measurement of abrasion
resistance of anodic oxidation
coatings—Part 2: Abrasive jet
abrasion resistance test**

ICS 25.220.20;77.120.10

Reference number : **JIS H 8682-2 : 2013 (E)**

H 8682-2 : 2013

Date of Establishment: 1999-08-20

Date of Revision: 2013-05-20

Date of Public Notice in Official Gazette: 2013-05-20

Investigated by: Japanese Industrial Standards Committee
Standards Board

Technical Committee on Non-Ferrous Metals

JIS H 8682-2:2013, First English edition published in 2015-03

Translated and published by: Japanese Standards Association
Mita MT Building, 3-13-12, Mita, Minato-ku, Tokyo, 108-0073 JAPAN

In the event of any doubts arising as to the contents,
the original JIS is to be the final authority.

© JSA 2015

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

KK/AT

PROTECTED BY COPYRIGHT

Contents

	Page
Introduction.....	1
1 Scope.....	1
2 Normative references	1
3 Terms and definitions	2
4 Feature.....	2
5 Summary.....	2
6 Test apparatus and measuring instruments	2
7 Test method.....	4
7.1 Standard specimen	4
7.2 Reference specimen	4
7.3 Test specimen.....	4
7.4 Test conditions	4
7.5 Procedure	5
8 Expression of test results.....	6
8.1 General.....	6
8.2 Wear time	7
8.3 Wear resistance	7
8.4 Wear resistance coefficient	7
8.5 Abrasive jet factor	7
8.6 Mean specific wear resistance	8
8.7 Relative mean specific wear resistance.....	8
9 Test report	9
Annex A (normative) Preparation of standard specimen (for ordinary coating)	10
Annex B (informative) Depth survey of wear resistance	12
Annex C (informative) Abrasive jet test apparatus	14
Annex JA (normative) Preparation of standard specimen (for hard coating).....	15
Annex JB (informative) Comparison table between JIS and corresponding International Standard	17

Foreword

This translation has been made based on the original Japanese Industrial Standard revised by the Minister of Economy, Trade and Industry through deliberations at the Japanese Industrial Standards Committee as the result of proposal for revision of Japanese Industrial Standard submitted by Japan Aluminium Products Association (JAPA)/Japanese Standards Association (JSA) with the draft being attached, based on the provision of Article 12 Clause 1 of the Industrial Standardization Law applicable to the case of revision by the provision of Article 14.

Consequently, **JIS H 8682-2:1999** is replaced with this Standard.

This **JIS** document is protected by the Copyright Law.

Attention is drawn to the possibility that some parts of this Standard may conflict with patent rights, applications for a patent after opening to the public or utility model rights. The relevant Minister and the Japanese Industrial Standards Committee are not responsible for identifying any of such patent rights, applications for a patent after opening to the public or utility model rights.

JIS H 8682 series consists of the following 3 parts under the general title “*Anodizing of aluminium and its alloys—Measurement of abrasion resistance of anodic oxidation coatings*”:

Part 1: Abrasive-wheel-wear abrasion resistance test

Part 2: Abrasive jet abrasion resistance test

Part 3: Falling sand abrasion resistance test

Anodizing of aluminium and its alloys— Measurement of abrasion resistance of anodic oxidation coatings—Part 2: Abrasive jet abrasion resistance test

Introduction

This Japanese Industrial Standard has been prepared based on the second edition of **ISO 8251** published in 2011 with some modifications of the technical contents.

The portions given sidelines or dotted underlines are the matters in which the contents of the corresponding International Standard have been modified. A list of modifications with the explanations is given in Annex JB.

1 Scope

This Standard specifies the test method for obtaining the wear characteristics such as wear resistance by jetting abrasive particles on the surface of anodic oxidation coatings exceeding 5 μm in thickness (hereafter referred to as “coatings”) applied to the products manufactured from aluminium and aluminium alloys (hereafter referred to as “products”) under a fixed pressure.

NOTE 1 There are an abrasive-wheel-wear abrasion resistance test, abrasive jet abrasion resistance test and falling sand abrasion resistance test in the test methods. In this Standard, an abrasive jet abrasion resistance test method is specified.

NOTE 2 The International Standard corresponding to this Standard and the symbol of degree of correspondence are as follows:

ISO 8251:2011 *Anodizing of aluminium and its alloys—Measurement of abrasion resistance of anodic oxidation coatings* (MOD)

The symbols which denote the degree of correspondence in the contents between the relevant International Standard and **JIS** are IDT (identical), MOD (modified), and NEQ (not equivalent) according to **ISO/IEC Guide 21-1**.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this Standard. The most recent editions of the standards (including amendments) indicated below shall be applied.

JIS C 1202 *Circuit testers*

JIS H 0201 *Glossary of terms used in the surface treatment of aluminium*

JIS H 8680-2 *Test methods for thickness of anodic oxide coatings on aluminium and aluminium alloys—Part 2: Eddy current method*

JIS R 6111 *Artificial abrasives*