

# JAPANESE INDUSTRIAL STANDARD

Translated and Published by Japanese Standards Association

JIS K 5516:2019

(JPMA/JSA)

Ready mixed paints (Synthetic resin type)

**ICS** 83.140.99; 87.040; 91.180

Reference number: JIS K 5516: 2019 (E)

K 5516: 2019

Date of Establishment: 1965-02-01

Date of Revision: 2019-03-20

Date of Public Notice in Official Gazette: 2019-03-20

Investigated by: Japanese Industrial Standards Committee

Standards Board for ISO area

Technical Committee on Chemical Products and

**Analytical Methods** 

JIS K 5516: 2019, First English edition published in 2019-11

Translated and published by: Japanese Standards Association Mita MT Building, 3-13-12, Mita, Minato-ku, Tokyo, 108-0073 JAPAN

In the event of any doubts arising as to the contents, the original JIS is to be the final authority.

© JSA 2019

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan HN

### Contents

	Page	
Introd	luction ····································	
1	Scope	
2	Normative references · · · · · · 1	
3	Terms and definitions · · · · · 3	
4	Classification · · · · 3	
5	Quality	
6	Reference sample $\cdots 4$	
7	Test methods ······5	
7.1	Sampling ······5	
7.2	Examination and preparation of sample for testing · · · · · · 5	
7.3	General conditions for tests · · · · · · · 5	
7.4	Condition inside container ······ 6	
7.5	Application property ······ 6	
7.6	Surface-drying property ······6	
7.7	Appearance of film · · · · · · · 7	
7.8	Contrast ratio ····································	
7.9	Accelerated yellowness ·····8	
7.10	Specular gloss ······8	
7.11	Recoatability ·····8	
7.12	Overcoatability ·····9	
7.13	Non-volatile matter content ·····9	
7.14	Salt water resistance ·····9	
7.15	Accelerated weathering resistance ·······10	
7.16	Natural weathering resistance ······11	
7.17	Class of formaldehyde emission from film · · · · · · 12	
8	Inspection · · · · · · · · · · · · · · · · · · ·	
9	Marking	
Annex A (normative) Application of sample using a film applicator ······14		
Annex B (informative) Number of test panels and test days necessary for the test of synthetic resin ready mixed paint16		

### Foreword

This Japanese Industrial Standard has been established by the Minister of Economy, Trade and Industry through deliberations at the Japanese Industrial Standards Committee as the result of proposal for revision of Japanese Industrial Standard submitted by Japan Paint Manufacturers Association (JPMA)/Japanese Standards Association (JSA) with the draft being attached, based on the provision of Article 12 Clause 1 of the Industrial Standardization Law applicable to the case of revision by the provision of Article 14. Consequently **JIS K 5516**:2014 is replaced with this Standard.

However, **JIS K 5516**:2014 may be applied in the **JIS** mark certification based on the relevant provisions of Article 19 Clause 1, etc. of the Industrial Standardization Law until March 19, 2020.

This **JIS** document is protected by the Copyright Law.

Attention is drawn to the possibility that some parts of this Standard may conflict with patent rights, applications for a patent after opening to the public or utility model rights. The relevant Minister and the Japanese Industrial Standards Committee are not responsible for identifying any of such patent rights, applications for a patent after opening to the public or utility model rights

## Ready mixed paints (Synthetic resin type)

JIS K 5516: 2019

### Introduction

This Japanese Industrial Standard was established in 1965 and has gone through seven revisions up to the present. The last revision was made in 2014 by issuing an amendment, and the revision at this time is to reflect the changes in and some deletions of quality requirement items, which have been made since 2014.

No corresponding International Standard has been established at this point.

### 1 Scope

This Japanese Industrial Standard specifies the requirements for synthetic resin ready mixed paint which is used as the intermediate coat or top coat of buildings (steel part and wooden part) and steel constructions.

NOTE The synthetic resin ready mixed paint is the air-drying type liquid coating prepared by kneading colour pigments, extender pigments, etc. with mainly long-oil phthalic resin varnish.

#### 2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this Standard. The most recent editions of the standards (including amendments) indicated below shall be applied.

JIS G 3141 Cold-reduced carbon steel sheet and strip			
JIS H 4000 Alu	minium and aluminium alloy sheets, strips and plates		
JIS K 5500 Glos	ssary of terms for coating materials		
JIS K 5600-1-1	$Testing \ methods \ for \ paints Part \ 1 : General \ rule \ Section \ 1 : \\ General \ test \ methods \ (conditions \ and \ methods)$		
JIS K 5600-1-2	$Testing \ methods \ for \ paints Part \ 1 : General \ rules Section \ 2 : \\ Sampling$		
JIS K 5600-1-3	Testing methods for paints — Part 1: General rule — Section 3: Examination and preparation of samples for testing		
JIS K 5600-1-4	Testing methods for paints — Part 1: General rule — Section 4: Standard panels for testing		
JIS K 5600-1-5	Testing methods for paints — Part 1: General rule — Section 5: Coating of test panel (brush application)		
JIS K 5600-1-6	Testing methods for paints — Part 1: General rule — Section 6: Temperatures and humidities for conditioning and testing		
JIS K 5600-1-7	Testing methods for paints — Part 1: General rule — Section 7:		