

JIS

JAPANESE
INDUSTRIAL
STANDARD

Translated and Published by
Japanese Standards Association

JIS K 5669 : 2008

(JPMA/JSA)

Synthetic resin emulsion putty

ICS 83.140.99 ; 87.040 ; 91.180

Reference number : JIS K 5669 : 2008 (E)

Date of Establishment: 1982-03-01

Data of Revision: 2008-12-20

Date of Public Notice in Official Gazette: 2008-12-22

Investigated by: Japanese Industrial Standards Committee

Standards Board

Technical Committee on Chemical Products

JIS K 5669 : 2008, First English edition published in 2009-07

Translated and published by: Japanese Standards Association
4-1-24, Akasaka, Minato-ku, Tokyo, 107-8440 JAPAN

In the event of any doubts arising as to the contents,
the original JIS is to be the final authority.

© JSA 2009

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

NH/HN

Contents

	Page
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Type and classification of formaldehyde emission grade	2
4.1 Type	2
4.2 Classification of formaldehyde emission grade	2
5 Quality	3
6 Evaluation sample	3
7 Test method	4
7.1 Sampling	4
7.2 Examination and preparation of sample for testing	4
7.3 General conditions for testing	4
7.4 Condition inside container	4
7.5 Application workability	4
7.6 Hard-dryability	5
7.7 Grindability	5
7.8 Overcoatability	6
7.9 Water resistance	6
7.10 Alkali resistance	7
7.11 Non-volatile matter content	8
7.12 Adhesive property	8
7.13 Low-temperature stability	9
8 Inspection	10
9 Marking	10
Annex A (informative) Test procedure	11

Foreword

This translation has been made based on the original Japanese Industrial Standard revised by the Minister of Economy, Trade and Industry through deliberations at the Japanese Industrial Standards Committee as the result of proposal for revision of Japanese Industrial Standard submitted by Japan Paint Manufacturers Association (JPMA) / Japanese Standards Association (JSA) with the draft being attached, based on the provision of Article 12 Clause 1 of the Industrial Standardization Law applicable to the case of revision by the provision of Article 14.

Consequently, **JIS K 5669:2003** is replaced with this Standard.

This **JIS** document is protected by the Copyright Law.

Attention is drawn to the possibility that some parts of this Standard may conflict with a patent right, application for a patent after opening to the public, utility model right or application for registration of utility model after opening to the public which have technical properties. The relevant Minister and the Japanese Industrial Standards Committee are not responsible for identifying the patent right, application for a patent after opening to the public, utility model right or application for registration of utility model after opening to the public which have the said technical properties.

Synthetic resin emulsion putty

1 Scope

This Japanese Industrial Standard specifies the synthetic resin emulsion putty (hereafter referred to as “putty”) to be used for making substrate when the surface of plywood, fibre reinforced cement board, gypsum board, mortar and concrete, etc. will be finished with synthetic resin emulsion paint. The putty shall not contain any of urea resins, melamine resins, urea and melamine cocondensation resins, phenol resins, resorcinol resins and formaldehyde based preservations.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this Standard. The most recent editions of the standards (including amendments) indicated below shall be applied.

- JIS A 5430 *Fiber reinforced cement boards*
- JIS G 4305 *Cold-rolled stainless steel plate, sheet and strip*
- JIS H 3100 *Copper and copper alloy sheets, plates and strips*
- JIS K 2235 *Petroleum waxes*
- JIS K 5500 *Glossary of terms for coating materials*
- JIS K 5600-1-1 *Testing methods for paints — Part 1 : General rule — Section 1 : General test methods (conditions and methods)*
- JIS K 5600-1-2 *Testing methods for paints — Part 1 : General rules — Section 2 : Sampling*
- JIS K 5600-1-3 *Testing methods for paints — Part 1 : General rule — Section 3 : Examination and preparation of samples for testing*
- JIS K 5600-1-6 *Testing methods for paints — Part 1 : General rule — Section 6 : Temperatures and humidities for conditioning and testing*
- JIS K 5600-1-8 *Testing methods for paints — Part 1 : General rule — Section 8 : Reference sample*
- JIS K 5600-4-3 *Testing methods for paints — Part 4 : Visual characteristics of film — Section 3 : Visual comparison of the colour of paints*
- JIS K 5600-5-7 *Testing methods for paints — Part 5 : Mechanical property of film — Section 7 : Adhesion test (Pull-off methods)*
- JIS K 5600-6-1 *Testing methods for paints — Part 6 : Chemical property of film — Section 1 : Resistance to liquids (General methods)*