

JIS

JAPANESE
INDUSTRIAL
STANDARD

Translated and Published by
Japanese Standards Association

JIS K 6256-1 : 2013

(JRMA/JSA)

**Rubber, vulcanized or thermoplastic —
Determination of adhesion strength —
Part 1: Adhesion to textile fabric**

ICS 83.060

Reference number : JIS K 6256-1 : 2013 (E)

PROTECTED BY COPYRIGHT

9 5

K 6256-1 : 2013

Date of Establishment: 2006-12-20

Date of Revision: 2013-09-20

Date of Public Notice in Official Gazette: 2013-09-20

Investigated by: Japanese Industrial Standards Committee

Standards Board

Technical Committee on Chemical Products

JIS K 6256-1 : 2013, First English edition published in 2015-05

Translated and published by: Japanese Standards Association
Mita MT Building, 3-13-12, Mita, Minato-ku, Tokyo, 108-0073 JAPAN

In the event of any doubts arising as to the contents,
the original JIS is to be the final authority.

© JSA 2015

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

NH/HN

PROTECTED BY COPYRIGHT

Contents

	Page
Introduction	1
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Principle	2
5 Test apparatus	3
5.1 Tensile test machine	3
5.2 Recorder	3
6 Calibration of test apparatus	3
7 Test piece	3
7.1 Shape and dimensions of test piece	3
7.2 Sampling/preparation of test piece	3
8 Number of test pieces	4
9 Time-interval between vulcanization or moulding and testing	4
10 Conditioning and test temperature	5
11 Operation method	5
12 Calculation	5
13 Expression of results	6
13.1 Adhesion strength	6
13.2 Type and expression of separation state	6
14 Test report	6
Annex A (normative) Calibration of test apparatus	8
Annex JA (informative) Comparison table between JIS and corresponding International Standard	10

Foreword

This translation has been made based on the original Japanese Industrial Standard revised by the Minister of Economy, Trade and Industry through deliberations at the Japanese Industrial Standards Committee as the result of proposal for revision of Japanese Industrial Standard submitted by The Japan Rubber Manufacturers Association (JRMA)/ Japanese Standards Association (JSA) with the draft being attached, based on the provision of Article 12 Clause 1 of the Industrial Standardization Law applicable to the case of revision by the provision of Article 14.

Consequently, **JIS K 6256-1: 2006** is replaced with this Standard.

This **JIS** document is protected by the Copyright Law.

Attention is drawn to the possibility that some parts of this Standard may conflict with patent rights, applications for a patent after opening to the public or utility model rights. The relevant Minister and the Japanese Industrial Standards Committee are not responsible for identifying any of such patent rights, applications for a patent after opening to the public or utility model rights.

JIS K 6256 series consists of the following 3 parts under the general title *Rubber, vulcanized or thermoplastic — Determination of adhesion strength*

Part 1: Adhesion to textile fabric

Part 2: Adhesion to a rigid substrate — 90° method

Part 3: Adhesion to metal — Two-plate method

Rubber, vulcanized or thermoplastic — Determination of adhesion strength — Part 1 : Adhesion to textile fabric

Introduction

This Japanese Industrial Standard has been prepared based on the fifth edition of ISO 36 published in 2011 with some modifications of the technical contents.

The portions given sidelines or dotted underlines are the matters in which the contents of the corresponding International Standard have been modified. A list of modifications with the explanations is given in Annex JA.

1 Scope

This Standard specifies the determination method of the adhesion strength of the composite comprising two plies of fabric bonded with vulcanized rubber or thermoplastic rubber, or fabric and vulcanized rubber or thermoplastic rubber bonded together.

This Standard is applicable to the composite to be tested being a plane or a cylinder-shape exceeding 50 mm in inside diameter.

This Standard is not applicable to the composite having sharp curve or angle. Also, this Standard is not applicable to the adhesion test for the vulcanized rubber- or plastics-coated fabrics and conveyer belts specified in JIS K 6404-5 and ISO 252.

NOTE : The International Standard corresponding to this Standard and the symbol of degree of correspondence are as follows :

ISO 36 : 2011 *Rubber, vulcanized or thermoplastic — Determination of adhesion to textile fabrics* (MOD)

The symbols which denote the degree of correspondence in the contents between the relevant International Standard and JIS are IDT (identical), MOD (modified), and NEQ (not equivalent) according to ISO/IEC Guide 21-1.

WARNING Persons using this Standard should be familiar with normal laboratory practice. This Standard does not purport to address all of the safety problems, if any, associated with its use. It is the responsibility of the user to establish appropriate safety and health practices.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this Standard. For standards with the year indication, only the editions of the indicated year shall be applied and the revisions (including amendments) made thereafter shall not be applied. For those without the indication of the year, the most recent edition (including amendments) shall be applied.