

JIS

JAPANESE
INDUSTRIAL
STANDARD

Translated and Published by
Japanese Standards Association

JIS K 6259-1 : 2015

(JRMA/JSA)

**Rubber, vulcanized or
thermoplastic—Determination of
ozone resistance—Part 1: Static
and dynamic strain testing**

ICS 83.060

Reference number : **JIS K 6259-1 : 2015 (E)**

K 6259-1 : 2015

Date of Establishment: 2015-09-24

Date of Public Notice in Official Gazette: 2015-09-24

Investigated by: Japanese Industrial Standards Committee
Standards Board for ISO area
Technical Committee on Chemical Products and
Analytical Methods

JIS K 6259-1:2015, First English edition published in 2016-08

Translated and published by: Japanese Standards Association
Mita MT Building, 3-13-12, Mita, Minato-ku, Tokyo, 108-0073 JAPAN

In the event of any doubts arising as to the contents,
the original JIS is to be the final authority.

© JSA 2016

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

NH/AT

PROTECTED BY COPYRIGHT

Contents

	Page
Introduction.....	1
1 Scope	1
2 Normative references.....	1
3 Terms and definitions	2
4 Principle	2
5 Apparatus	4
6 Calibration of test apparatus	8
7 Test pieces	8
7.1 General	8
7.2 Wide test piece	9
7.3 Narrow test piece	9
7.3A Preparation of the test pieces	9
7.3B Measuring the thickness and width of the test pieces	9
7.3C Making method of bench mark for measuring tensile strain	9
8 Conditioning	10
8.1 Conditioning in the unstrained state	10
8.1A Standard laboratory temperature	10
8.1B Storage of test specimens and test pieces	10
8.1C Conditioning of test pieces.....	10
8.2 Conditioning in the strained state (for static strain testing only)	10
9 Test conditions.....	10
9.1 Ozone concentration	10
9.2 Temperature of test	11
9.3 Relative humidity	11
9.4 Maximum elongation	11
10 Static strain testing.....	11
10.1 General	11
10.2 Choice of procedure.....	12
11 Dynamic strain testing.....	13
11.1 General	13
11.2 Continuous dynamic exposure.....	14
11.3 Intermittent dynamic exposure.....	15
12 Expression of results	16
12.1 Procedure A (Crack condition observation procedure).....	16

12.2	Procedure B (Crack appearance time measuring procedure)	16
12.3	Procedure C (Threshold strain and limiting threshold strain measuring procedure).....	16
13	Test report	17
Annex A (informative)	Ozone cracking—Explanatory notes	19
Annex B (normative)	Calibration schedule	21
Annex C (informative)	Ozone cracking—Rating scales	23
Annex JA (normative)	Estimate of the degree of cracking	24
Annex JB (informative)	Comparison table between JIS and corresponding International Standard	26

Foreword

This translation has been made based on the original Japanese Industrial Standard established by the Minister of Economy, Trade and Industry through deliberations at the Japanese Industrial Standards Committee according to the proposal for establishment of Japanese Industrial Standard submitted by The Japan Rubber Manufacturers Association (JRMA)/Japanese Standards Association (JSA) with the draft being attached, based on the provision of Article 12 Clause 1 of the Industrial Standardization Law.

This **JIS** document is protected by the Copyright Law.

Attention is drawn to the possibility that some parts of this Standard may conflict with patent rights, applications for a patent after opening to the public or utility model rights. The relevant Minister and the Japanese Industrial Standards Committee are not responsible for identifying any of such patent rights, applications for a patent after opening to the public or utility model rights.

JIS K 6259 series consists of the following 2 parts under the general title “*Rubber, vulcanized or thermoplastic—Determination of ozone resistance*”:

Part 1: Static and dynamic strain testing

Part 2: Determination of the ozone concentration

Rubber, vulcanized or thermoplastic— Determination of ozone resistance— Part 1: Static and dynamic strain testing

Introduction

This Japanese Industrial Standard has been prepared based on the fifth edition of **ISO 1431-1** published in 2012 with some modifications of the technical contents.

The portions given sidelines or dotted underlines are the matters in which the contents of the corresponding International Standard have been modified. A list of modifications with the explanations is given in Annex JB.

1 Scope

This Standard specifies the test method for the determination of the ozone resistance of vulcanized or thermoplastic rubber under static and dynamic strain testing.

NOTE : The International Standard corresponding to this Standard and the symbol of degree of correspondence are as follows.

ISO 1431-1:2012 *Rubber, vulcanized or thermoplastic—Resistance to ozone cracking—Part 1: Static and dynamic strain testing* (MOD)

In addition, symbols which denote the degree of correspondence in the contents between the relevant International Standard and **JIS** are IDT (identical), MOD (modified), and NEQ (not equivalent) according to **ISO/IEC Guide 21-1**.

WARNING Persons using this Standard should be familiar with normal laboratory practice. This Standard does not purport to address all of the safety problems, if any, associated with its use. It is the responsibility of the user of this Standard to establish appropriate safety and health practices.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this Standard. For standards with the year indication, only the editions of the indicated year shall be applied and the revisions (including amendments) made thereafter shall not be applied. For those without the indication of the year, the most recent edition (including amendments) shall be applied.

JIS K 6200 *Rubber—Vocabulary*

JIS K 6250 *Rubber—General procedures for preparing and conditioning test pieces for physical test methods*

NOTE : Corresponding international Standard: ISO 23529 *Rubber—General procedures for preparing and conditioning test pieces for physical test methods* (MOD)