



JAPANESE INDUSTRIAL STANDARD

**Testing methods for
thermosetting plastics**

JIS K 6911-1995

JIS K 6911 : 1995 has been revised under date of February 20, 2006. The revised items are included in Amendment 1.

Translated and Published

by

Japanese Standards Association

**In the event of any doubt arising,
the original Standard in Japanese is to be final authority**

Errata for JIS (English edition) are printed in *Standardization Journal*, published monthly by the Japanese Standards Association.

Errata will be provided upon request, please contact:
Business Department,
Japanese Standards Association
4-1-24, Akasaka, Minato-ku,
Tokyo, JAPAN 107
TEL. 03-3583-8002
FAX. 03-3583-0462

Errata are also provided to subscribers of JIS (English edition) in *Monthly Information*.

Contents

	Page
1. Scope	1
2. Definitions	1
3. Method of sampling and making test pieces	5
3.1 Method of sampling	5
3.2 Method of making test pieces	5
4. Test items	5
5. Test method	14
5.1 General conditions for tests	14
5.2 Apparent density and bulk factor	14
5.3 Flow	17
5.4 Mouldability (moulding material)	20
5.5 Dimensions	21
5.6 Warping rate or twisting rate (laminated sheets)	24
5.7 Mould shrinkage coefficient and rate of shrinkage on heating (moulding material)	25
5.8 Withstand voltage (moulding material)	28
5.9 Withstand voltage (laminated rods)	29
5.10 Flatwise withstand voltage	30
5.11 Edgewise withstand voltage	32
5.12 Insulation resistance	35
5.13 Resistivity	39
5.14 Dielectric constant and dielectric dissipation factor	41
5.15 Arc resistance (moulding materials)	48
5.16 Hardness (moulding material and laminated sheets)	50
5.17 Flexural strength and bending modulus of elasticity	52
5.18 Tensile strength	58
5.19 Compressive strength	61
5.20 Charpy impact strength (moulding material)	64
5.21 Izod impact strength (laminated sheet)	68
5.22 Bonding strength (laminated sheets)	71
5.23 Appearance after heating	72
5.24 Burning resistance	73
5.25 Thermal expansion	77
5.26 Water absorption	78
5.27 Boiling water absorption (moulding material)	80

K 6911-1995

5.28	Specific gravity.....	81
5.29	Resistance to acetone (for phenolic resin only).....	82
5.30	Resistance to boiling water (moulding material).....	83
5.31	Resistance to sulfuric acid (for melamine resin moulding material only)	83
5.32	Chemical resistance (moulding material)	84
5.33	Free water content (moulding material)	86
5.34	Flexural strength under heat (laminated sheets)	86
5.35	Deflection temperature under load	87

JAPANESE INDUSTRIAL STANDARD

J I S

Testing methods for thermosetting plastics

K 6911-1995

1. Scope This Japanese Industrial Standard specifies the general methods of testing thermosetting plastics.

Remarks 1. The following standards are cited in this Standard.

- JIS B 1352 Taper pins
- JIS B 4410 Taper pin reamers
- JIS B 7502 Micrometer callipers
- JIS B 7503 Dial gauges
- JIS B 7507 Vernier, dial and digital callipers
- JIS B 7512 Steel tape measures
- JIS B 7513 Precision surface plates
- JIS B 7514 Steel straightedges
- JIS B 7516 Metal rules
- JIS B 7601 Trip balances
- JIS B 7726 Rockwell and Rockwell superficial hardness testing machines
- JIS C 1102 Electrical indicating instruments
- JIS C 1302 Insulation resistance testers
- JIS C 2320 Electrical insulating oils
- JIS G 4051 Carbon steels for machine structural use
- JIS K 8034 Acetone
- JIS K 8951 Sulfuric acid
- JIS R 3503 Glass apparatus for chemical analysis
- JIS R 6252 Abrasive papers
- JIS Z 8101 Glossary of terms used in quality control
- JIS Z 8401 Rules for rounding off of numerical values
- JIS Z 8801 Test sieves

2. The units and numerical values given in { } in this Standard are in accordance with the traditional unit system and appended for informative reference.

2. Definitions For the purpose of this Standard, the definitions of principal terms are as follows:

- (1) apparent density The mass of moulding material per unit volume.
- (2) bulk factor The quotient of the density of moulding product divided by the apparent density of the moulding material used for the moulding product. The bulk factor is equal to the quotient of the volume of the moulding material required for moulding divided by the volume of the moulded product.