

JIS

JAPANESE
INDUSTRIAL
STANDARD

Translated and Published by
Japanese Standards Association

JIS S 2148 : 2013

(JIA)

Gas cylinders for portable gas cooker

S 2148 : 2013

Date of Establishment: 1991-07-01

Date of Revision: 2013-02-20

Date of Public Notice in Official Gazette: 2013-02-20

Investigated by: Japanese Industrial Standards Committee

Standards Board

Technical Committee on Consumer Life Products

JIS S 2148 : 2013, First English edition published in 2015-09

Translated and published by: Japanese Standards Association
Mita MT Building, 3-13-12, Mita, Minato-ku, Tokyo, 108-0073 JAPAN

In the event of any doubts arising as to the contents,
the original JIS is to be the final authority.

© JSA 2015

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

HN

PROTECTED BY COPYRIGHT

Contents

	Page
Introduction	1
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Performance	3
5 Filled LPG	3
5.1 Component	3
5.2 Nominal LPG volume	3
5.3 Odor	4
6 Construction	4
7 Dimensions	4
7.1 Dimensions of cartridge and cartridge valve	4
7.2 Compressive (stroke) dimension and initial injection stroke dimension of cartridge valve	6
8 Material	6
8.1 Material of cartridge body	6
8.2 Material of stem	7
9 Test methods	8
9.1 Test instruments and apparatus	8
9.2 Tests for construction, dimensions and materials	8
9.3 Gas resistance test	9
9.4 Ozone resistance test	9
9.5 Gas tightness test	9
9.6 Pressure resistance test	9
9.7 Stem functioning load test	10
9.8 Repeated use test	10
9.9 LPG component test	10
9.10 Filled LPG mass test	10
9.11 Odorous test	10
9.12 Test of compressive (stroke) dimension and initial injection stroke dimension of cartridge valve	11
9.13 Initial partial air pressure	11
9.14 Valve flow rate	11
9.15 Flange strength	12
10 Inspection	12

11	Marking	13
Annex A (normative)	Measuring methods for LPG odor	15

Foreword

This translation has been made based on the original Japanese Industrial Standard revised by the Minister of Economy, Trade and Industry through deliberations at the Japanese Industrial Standards Committee as the result of proposal for revision of Japanese Industrial Standard submitted by Japan Gas Appliances Inspection Association (JIA) with the draft being attached, based on the provision of Article 12 Clause 1 of the Industrial Standardization Law applicable to the case of revision by the provision of Article 14.

Consequently, **JIS S 2148:1998** is replaced with this Standard.

This **JIS** document is protected by the Copyright Law.

Attention is drawn to the possibility that some parts of this Standard may conflict with patent rights, applications for a patent after opening to the public or utility model rights. The relevant Minister and the Japanese Industrial Standards Committee are not responsible for identifying any of such patent rights, applications for a patent after opening to the public or utility model rights.

Gas cylinders for portable gas cooker

Introduction

This Japanese Industrial Standard was established in 1991 and has gone through two revisions up to the present. The last revision was made in 1998 and the revision at this time is to respond to the reduction of the dimensional tolerances and clarification of the inspection methods for the purpose of promoting the standardization, as well as addition of the flange strength test method and the marking requirements.

No International Standard corresponding to this Standard has been established at this point.

1 Scope

This Standard specifies cartridges filled up with liquefied petroleum gas (LPG) used as a component of portable gas cookers.

The portable gas cookers are those specified in **JIS S 2147**.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this Standard. The most recent editions of the standards (including amendments) indicated below shall be applied.

- JIS C 3101 *Hard-drawn copper wires for electrical purposes*
- JIS C 3102 *Annealed copper wires for electrical purposes*
- JIS G 3302 *Hot-dip zinc-coated steel sheet and strip*
- JIS G 3303 *Tinplate and blackplate*
- JIS G 3313 *Electrolytic zinc-coated steel sheet and strip*
- JIS G 3314 *Hot-dip aluminium-coated steel sheet and strip*
- JIS G 3446 *Stainless steel pipes for machine and structural purposes*
- JIS G 3459 *Stainless steel pipes*
- JIS G 4303 *Stainless steel bars*
- JIS G 4304 *Hot-rolled stainless steel plate, sheet and strip*
- JIS G 4305 *Cold-rolled stainless steel plate, sheet and strip*
- JIS G 4308 *Stainless steel wire rods*
- JIS G 4313 *Cold rolled stainless steel strip for springs*
- JIS G 4314 *Stainless steel wires for springs*
- JIS H 3100 *Copper and copper alloy sheets, plates and strips*