



JAPANESE
INDUSTRIAL
STANDARD

Translated and Published by
Japanese Standards Association

JIS X 6319-4 : 2016

(JICSAP/JSA)

**Specification of implementation for
integrated circuit cards—
Part 4: High speed proximity cards**

ICS 35.240.15

Reference number : **JIS X 6319-4 : 2016 (E)**

Date of Establishment: 2005-07-20

Date of Revision: 2016-03-22

Date of Public Notice in Official Gazette: 2016-03-22

Investigated by: Japanese Industrial Standards Committee
Standards Board for IEC area
Technical Committee on Information

JIS X 6319-4:2016, First English edition published in 2017-01

Translated and published by: Japanese Standards Association
Mita MT Building, 3-13-12, Mita, Minato-ku, Tokyo, 108-0073 JAPAN

In the event of any doubts arising as to the contents,
the original JIS is to be the final authority.

© JSA 2017

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

AT

Contents

	Page
Introduction.....	1
1 Scope	1
2 Normative references	2
3 Terms and definitions, abbreviations and symbols.....	3
3.1 Terms and definitions.....	3
3.2 Abbreviations and symbols	6
4 Physical characteristics	6
4.1 General physical characteristics	6
4.2 Dimensions	7
4.3 Surface condition	7
4.4 Substrate material	7
4.5 Additional physical characteristics	7
5 Air interface	9
5.1 Power transfer	9
5.2 Communication signal interface from PCD to PICC	9
5.3 Communication signal interface from PICC to PCD	11
6 Character, frame format and response timing	11
6.1 Character transmission	12
6.2 Frame format	12
6.3 PICC response timing.....	14
7 Overview of command message and response message.....	15
8 Initialization, anticollision and state transition	16
8.1 Communication initialization	16
8.2 Anticollision sequence	17
8.3 State of PICC	17
8.4 Anticollision response rule.....	21
8.5 REQ command	21
8.6 REQ response (ATQ).....	23
8.7 WUP command	26
8.8 WUP response	27
8.9 HLT command	27
8.10 HLT response	27
8.11 ATTR command	28
8.12 ATTR response	29
9 File.....	31

9.1	File organization	31
9.2	File types	32
9.3	Organization of files	34
9.4	Block	35
9.5	Access type to service file	35
10	Command and response	41
10.1	List of commands and responses	41
10.2	PICC mode transition	42
10.3	RequestService command and response	43
10.4	RequestResponse command and response	44
10.5	Read command and response	44
10.6	Write command and response	47
10.7	Authentication1 command and Authentication2 command	48
10.8	SecureRead command and response	50
10.9	SecureWrite command and response	50
10.10	Vendor unique command and response	51
10.11	Extended command and response	51
10.12	NewAuthentication1 command and response	52
10.13	NewAuthentication2 command and response	52
10.14	NewSecureRead command and response	53
10.15	NewSecureWrite command and response	54
Annex A (informative)	Security	55
Annex B (informative)	Examples of command sequence	60
Annex C (informative)	Endian format	75
Annex D (normative)	PICC test methods	76
Annex E (normative)	PCD test methods	107
Annex F (informative)	Implementation of JIS X 6319-4 on JIS X 5211 conformant device	120

Foreword

This translation has been made based on the original Japanese Industrial Standard revised by the Minister of Economy, Trade and Industry through deliberations at the Japanese Industrial Standards Committee as the result of proposal for revision of Japanese Industrial Standard submitted by Japan IC Card System Application Council (JICSAP)/Japanese Standards Association (JSA) with the draft being attached, based on the provision of Article 12 Clause 1 of the Industrial Standardization Law applicable to the case of revision by the provision of Article 14.

Consequently **JIS X 6319-4**:2010 is replaced with this Standard.

This **JIS** document is protected by the Copyright Law.

Attention is drawn to the possibility that some parts of this Standard may conflict with patent rights, applications for a patent after opening to the public or utility model rights. The relevant Minister and the Japanese Industrial Standards Committee are not responsible for identifying any of such patent rights, applications for a patent after opening to the public or utility model rights.

JIS X 6319 series consists of the following four parts under the general title “*Specification of implementation for integrated circuit cards*”:

Part 1: Integrated circuit cards with contacts

Part 2: Proximity cards

Part 3: Common commands for interchange

Part 4: High speed proximity cards

Specification of implementation for integrated circuit cards— Part 4: High speed proximity cards

Editor's note : This English-translated edition includes some discrepancies from the original Japanese edition, which resulted from correction of errors or modifications made in the process of editing.

Introduction

This Japanese Industrial Standard has been prepared to specify the high speed contactless proximity integrated circuit cards (hereafter referred to as cards or PICCs) and the proximity coupling devices.

In order to provide the further details for interoperability of contactless interfaces (i.e. interfaces which do not use the conductive contact for signal communication or for power supply to the PICC), this Standard provides implementation specifications. Use of new standards in building and operating integrated circuit card systems is in no way constricted because contactless proximity integrated circuit cards have the potential to be used for a variety of applications and systems, while the performance of IC chips, such as power consumption, is constantly being improved by technological advances. Consideration is also given to the possibility that integrated circuit cards with or without contacts may be integrated into the same system.

The PICCs offer the functionality for:

- processing multiple files at one time;
- ensuring a transaction integrity with internal add-subtract calculation;
- bit coding for stable communication;
- response time parameters which enable timeout management for each command;
- and command recognition assuming power disruption during processing.

The PICCs are used in systems such as electronic ticketing at railway stations and event sites, which require high-speed processing of accesses during user's moving.

No International Standard corresponding to this Standard has been established at this point. Instead, **JIS X 5211** specifies the compatible proximity interface (only for contactless part).

1 Scope

This Standard specifies the physical characteristics, air interface, transmission protocols, file structure, commands and the like, which are used by high-speed proximity integrated circuit cards.

The accessing method for files that require authentication in the PICC defined by this Standard is described in Annex A (informative).

Examples of access to the PICC defined by this Standard are described in Annex B (informative) so that a reader of this Standard understands the usage of this Standard.